


**KEMET Part Number: TEPSLB21A336M8R**  
(PSLB21A336M8R-T&R)

**KEMET**

a YAGEO company

PS/L, Tantalum, Polymer Tantalum, 33 uF, 20%, 10 VDC, SMD, Molded, Polymer, Low ESR, 150 mOhms, 3528, Height Max = 2mm



**General Information**

<b>Series:</b>	PS/L
<b>Dielectric:</b>	Polymer Tantalum
<b>Style:</b>	SMD Chip
<b>Description:</b>	SMD, Molded, Polymer, Low ESR
<b>Features:</b>	Low ESR
<b>RoHS:</b>	Yes
<b>Termination:</b>	Tin
<b>AEC-Q200:</b>	No

**Dimensions**

<b>Footprint</b>	3528
<b>L</b>	3.5mm +/-0.2mm
<b>W</b>	2.8mm +/-0.2mm
<b>H</b>	1.9mm +/-0.1mm
<b>S</b>	0.8mm +/-0.2mm
<b>F</b>	2.2mm +/-0.1mm

**Specifications**

<b>Capacitance:</b>	33 uF
<b>Capacitance Tolerance:</b>	20%
<b>Voltage DC:</b>	10 VDC (105°C), 13 VDC (Surge)
<b>Temperature Range:</b>	-55/+105°C
<b>Rated Temperature:</b>	105°C
<b>Dissipation Factor:</b>	8%
<b>Failure Rate:</b>	N/A
<b>Resistance:</b>	150 mOhms (25C, 100kHz)
<b>Ripple Current:</b>	753 mAmps (25C, 100kHz)
<b>Leakage Current:</b>	33 uA

**Packaging Specifications**

<b>Packaging:</b>	T&R, 178mm
-------------------	------------

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

**KEMET**

a YAGEO company

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)