
## KEMET Part Number: PMR209MC6100M330R19T0

(P409CP104M250LH331)



PMR209, Film, Metallized Paper, Resistor/Capacitor, 0.1 uF, 20%, 630 VDC, 85°C, Lead Spacing = 20.3mm



Dimensions		
L	24mm MAX	
Н	16.5mm MAX	
Т	11.3mm MAX	
S	20.3mm +0.6/-0.1mm	
H0	18.5mm +/-0.5mm	
F	0.8mm +/-0.05mm	

Packaging Specifications		
Packaging:	T&R	
Packaging Quantity:	180	

General Information		
Series:	PMR209	
Dielectric:	Metallized Paper	
Style:	Radial	
Features:	RC Unit approved	
RoHS:	Yes	
Lead:	Wire Leads	
Qualifications:	ENEC, UL, cUL	
AEC-Q200:	No	
Construction:	Molded	
Miscellaneous:	Resistor= 330 Ohms.	
Notes:	Not For New Design, Please Use The New P409 Series @ 275 VAC.	

Specifications		
Capacitance:	0.1 uF	
Capacitance Tolerance:	20%	
Voltage AC:	250 VAC	
Voltage DC:	630 VDC	
Temperature Range:	-40/+85°C	
Rated Temperature:	85°C	
Insulation Resistance:	3 GOhms	
Safety Class:	X2	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



© 2006 - 2022 KEMET

## 单击下面可查看定价,库存,交付和生命周期等信息

## >>KEMET(基美)