
KEMET Part Number: M49470R01126KCN

(L1RN302126KB65)



KPS LDD Mil SMPS PRF49470, Ceramic, 12 uF, 10%, 200 VDC, BR, N/A



Dimensions		
D	25.715mm +/-1.585mm	
L	6.35mm MIN	
Т	1.397mm MAX	
S	2.54mm TYP	
F	0.254mm +/-0.051mm	
A	16.51mm MAX	
С	11.43mm +/-0.635mm	
E	12.7mm MAX	
G	1.4mm +/-0.25mm	
LO	1.586mm MAX	
LW	0.508mm +/-0.051mm	

Packaging Specifications		
Packaging:	Waffle, Box	
Packaging Quantity:	28	

General Information	
Series:	KPS LDD Mil SMPS PRF49470
Style:	Leaded Stacked Chip
Description:	Low ESR, High Current Stacked Ceramic Chips
Features:	Low ESR, High Current
RoHS:	No
Prop 65:	warning: Cancer and reproductive harm - www.p65warnings.ca.gov.
SCIP Number:	2499890a-0e07-42ff-98a1- bd02d3b7c2ec
Termination:	60/40 Solder Coated
Lead:	Wire Leads
Failure Rate:	N/A
Testing and Reliability:	Level B
Qualifications:	MIL-PRF-49470
AEC-Q200:	No
Notes:	Note: Number of chips in stack depends on design. Note: Lead alignment within pin rows shall be within ±.0.13 mm.

Specifications	
Capacitance:	12 uF
Capacitance Tolerance:	10%
Voltage DC:	200 VDC
Dielectric Withstanding Voltage:	500 VDC
Temperature Range:	-55/+125°C
Temperature Coefficient:	BR
Dissipation Factor:	2.5%
Insulation Resistance:	83.333 MOhms

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)