



Click [here](#) for the 3D model.

Dimensions	
L	180mm MIN
W	85mm MIN
H	60mm MIN
L1	115mm MIN
W1	100mm MIN
W2	115mm MIN
Z	19mm MIN
K	6.5mm MIN
M (Earth)	Threaded Studs M6

Packaging Specifications	
Packaging	Bulk
Packaging Quantity	1

General Information	
Series	FLLE2-AN
Style	Chassis Mount
Description	Single Phase Chassis Mount Filters
Features	Single Phase
Phase	Single-phase
RoHS	Yes
Terminal Type	Threaded Studs M6

Specifications	
Voltage AC	300 VAC
Rated Frequency	50-60 Hz
Rated Current	63 A
Rated Temperature	40°C
Temperature Range	-25/+100°C
Climate Category	25/100/21

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)