



Click [here](#) for the 3D model.

### Dimensions

|    |                 |
|----|-----------------|
| L  | 10.6mm +/-0.3mm |
| W  | 5.7mm +/-0.3mm  |
| H  | 8.8mm MAX       |
| LL | 3.4mm NOM       |
| S  | 3.2mm +/-0.15mm |
| S1 | 2.2mm +/-0.15mm |
| F  | 0.8mm +/-0.1mm  |
| F1 | 3.1mm +/-0.1mm  |

### Packaging Specifications

Packaging

T&R

### General Information

|             |   |
|-------------|---|
| Series      | UB2   |
| Style       | SMD   |
| Description | Miniature Signal Relay, Non-latch Low Power Consumption |
| Features    | Super-Compact Size, Flat-Package                        |
| RoHS        | Yes   |
| Coil Type   | Single Coil (Non-Latching)                              |

### Specifications

|                         |                                      |
|-------------------------|--------------------------------------|
| Temperature Range       | -40/+85°C                            |
| Coil Voltage            | 5 V                                  |
| Coil Resistance         | 250 Ohms +/-10%                      |
| Contact Form            | 2 Form C (DPDT)                      |
| Contact Material        | Silver Alloy With Gold Alloy Overlay |
| Voltage Characteristics | 3.75 (Operate) / 0.5 (Release)       |
| Switching Power         | 30 W, 37.5 VA                        |
| Switching Voltage DC    | 220 V                                |
| Switching Voltage AC    | 250 VAC                              |
| Switching Current       | 1A                                   |
| Contact Current Class   | >10A                                 |
| Carrying Current        | 1Amps                                |
| Contact Resistance      | 100 mOhms                            |
| Operation Time          | Approximately 2ms                    |
| Release Time            | Approximately 1ms                    |
| Insulation Resistance   | 1 GOhms                              |
| Withstanding Voltage    | 1000 VAC (1min) 1500 V Surge         |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)