


T322B685K010AS7200

Aliases (T322B685K010AS7241, T322B685K010ASTR)

T322, Tantalum, MnO2 Tantalum, Commercial Grade, 6.8 uF, 10%, 10 VDC, 6 Ohms



END VIEW

Click here for the 3D model.

Dimensions	
D	2.79mm MAX
L	7.37mm MAX
LL	25.4mm MIN
F	0.51mm +/-0.05mm

Packaging Specifications		
Packaging	T&R, 305mm, Class I, B = 52.4mm	
Packaging Quantity	1000	

General Information		
Series	T322	
Dielectric	MnO2 Tantalum	
Style	Axial	
Description	Axial, Solid Tantalum, Molded, Military (Non-ER), Low ESR	
Features	Low ESR	
RoHS	No	
Prop 65	★ WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov.	
SCIP Number	1f352243-82e7-4839-9036-6c061d7f7da2	
Termination	Lead (SnPb)	
Lead	Wire Leads	
AEC-Q200	No	
Notes	Uninsulated.	
Shelf Life	156 Weeks	

Specifications	
Capacitance	6.8 uF
Capacitance Tolerance	10%
Voltage DC	10 VDC (85C), 6.67 VDC (125C Surge), 0.1 VDC (125C Reverse)
Temperature Range	-55/+125°C
Rated Temperature	85°C
Dissipation Factor	6%
Resistance	6 Ohms (100kHz)
Leakage Current	0.5 uA (25°C)

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)