

AxiMax 400 Comm X7R, Ceramic, 0.033 uF, 5%, 100 VDC, X7R, AxiMax, Commercial Standard



| Dimensions |                        |
|------------|------------------------|
| D          | 2.54mm MAX             |
| L          | 5.08mm MAX             |
| F          | 0.51mm +0.025/-0.076mm |
| B          | 52.4mm +/-1.5mm        |

| Packaging Specifications |            |
|--------------------------|------------|
| Packaging:               | T&R, 305mm |
| Packaging Quantity:      | 5000       |

| General Information |                             |
|---------------------|-----------------------------|
| Series:             | AxiMax 400 Comm X7R         |
| Description:        | AxiMax, Commercial Standard |
| RoHS:               | Yes                         |
| Termination:        | Tin                         |
| AEC-Q200:           | No                          |
| Halogen Free:       | Yes                         |

| Specifications  |   |
|---|---|
| Capacitance:  | 0.033 uF  |
| Measurement Condition:  | 1 kHz 1.0Vrms                                   |
| Capacitance Tolerance:  | 5%  |
| Voltage DC:   | 100 VDC   |
| Dielectric Withstanding Voltage:                                    | 250 VDC   |
| Temperature Range:  | -55/+125°C                                      |
| Temperature Coefficient:  | X7R   |
| Capacitance Change with Reference to +25°C and 0 VDC Applied (TCC): | 0.15, 1kHz 1.0Vrms                              |
| Dissipation Factor:   | 2.5% 1 kHz 1.0Vrms                              |
| Aging Rate:   | 3% Loss/Decade Hour: Referee Time is 1000 Hours |
| Insulation Resistance:  | 30.3 GOhms                                      |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)

[>>点击查看相关商品](#)