
KEMET Part Number: R73QI1330JE30M

(73QI1330JE30M)



R73, Film, Film/Foil Polypropylene, Automotive Grade, 3300 pF, 20%, 1000 VDC, 85°C, Lead Spacing = 15mm



General Information		
Series:	R73	
Dielectric:	Film/Foil Polypropylene	
Style:	Radial	
Features:	Automotive Grade, Pulse	
RoHS:	Yes	
Lead:	Wire Leads	
Qualifications:	AEC-Q200	
AEC-Q200:	Yes	
Miscellaneous:	Above 85C DC And AC Voltage Derating Is 1.25%/C.	

28000 V/us

10 nH

Max dV/dt: Inductance:

Dimensions		
L	18mm +0.3/-0.5mm	
Н	11mm +0.1/-0.5mm	
Т	5mm +0.2/-0.5mm	
S	15mm +/-0.4mm	
LL	4mm +0.5mm	
F	0.8mm +/-0.05mm	

		Specifications	
mm +0.3/-0.5mm		Capacitance:	3300 pF
mm +0.1/-0.5mm		•	20%
nm +0.2/-0.5mm		Capacitance Tolerance:	
.5mm +/-0.4mm		Voltage AC:	400 VAC
		Voltage DC:	1000 VDC
4mm +0.5mm 8mm +/-0.05mm	Temperature Range:	-55/+105°C	
	Rated Temperature:	85°C	
		Dissipation Factor:	0.03% 1kHz, 0.04% 10kHz, 0.1% 100kHz
ations		Insulation Resistance:	100 GOhms

Packaging Specifications		
Packaging:	Bulk, Bag	
Packaging Quantity:	2000	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)