

R76TW3820SE30J

Aliases (76TW3820SE30J)

R76, Film, Double Metallized Polypropylene, General Purpose, 0.82 uF, 5%, 1600 VDC, 85°C, Lead Spacing = 37.5mm



Click [here](#) for the 3D model.

Dimensions

L	41.5mm +0.3/-0.7mm
H	44mm +0.1/-0.7mm
T	24mm +0.3/-0.7mm
S	37.5mm +/-0.4mm
LL	4mm +2mm
F	1mm +/-0.05mm

Packaging Specifications

Packaging	Tray
Packaging Quantity	108

General Information

Series	R76
Dielectric	Double Metallized Polypropylene
Style	Radial
Features	Pulse
RoHS	Yes
Lead	Cut
AEC-Q200	No

Specifications

Capacitance	0.82 uF
Capacitance Tolerance	5%
Voltage AC	650 VAC
Voltage DC	1600 VDC
Temperature Range	-55/+110°C
Rated Temperature	85°C
Dissipation Factor	0.03% 1kHz, 0.06% 10kHz
Insulation Resistance	36.58537 GOhms
Max dV/dt	1200 V/us
Resistance	5.82 mOhms (100kHz)
Ripple Current	14.1 Amps (100kHz 85C), 984 Amps (Peak)
Inductance	20 nH

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)