


C44U_M, Film, Metallized Polypropylene, DC Link, 1100 uF, 10%, 1100 VDC



General Information	
Series:	C44U_M
Dielectric:	Metallized Polypropylene
Style:	Can
Features:	DC Filtering, Energy Storage
RoHS:	Yes
Lead:	Screw Terminals M6
AEC-Q200:	No
Miscellaneous:	Thermal Resistance = 2.1 C/W. Weight = 11500 grams.

Dimensions	
D	116mm +2mm
L	233mm +/-2mm
L1	236mm +/-2mm
S	50mm +/-0.3mm

Packaging Specifications	
Mounting:	Bolt - M12x16
Packaging:	Bulk, Bag
Packaging Quantity:	4

Specifications	
Capacitance:	1100 uF
Capacitance Tolerance:	10%
Voltage DC:	1100 VDC
Temperature Range:	-40/+85°C
Rated Temperature:	75°C
Insulation Resistance:	0.03 MOhms
Max dV/dt:	9 V/us
Resistance:	1.4 mOhms (10kHz)
Ripple Current:	100 Amps (10kHz 40C), 9750 Amps (Peak)
Inductance:	75 nH

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)