

R75, Film, Metallized Polypropylene, General Purpose, 12 uF, 5%, 400 VDC, 85°C, Lead Spacing = 37.5mm



General Information	
Series:	R75
Dielectric:	Metallized Polypropylene
Style:	Radial
Features:	Pulse
RoHS:	Yes
Lead:	Cut
AEC-Q200:	No
Miscellaneous:	Above 85C DC And AC Voltage Derating Is 1.25%/C.

Dimensions	
L	41.5mm +0.3mm
H	44mm +0.1mm
T	24mm +0.3mm
S	37.5mm +/-0.4mm
LL	4mm +2mm
F	1mm +/-0.05mm

Specifications	
Capacitance:	12 uF
Capacitance Tolerance:	5%
Voltage AC:	220 VAC
Voltage DC:	400 VDC
Temperature Range:	-55/+105°C
Rated Temperature:	85°C
Dissipation Factor:	0.1% 1kHz
Insulation Resistance:	2.5 GOhms
Max dV/dt:	70 V/us
Ripple Current:	Amps (100kHz 85C) Amps (Peak)
Inductance:	20 nH

Packaging Specifications	
Packaging:	Tray
Packaging Quantity:	108

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)