



Click [here](#) for the 3D model.

Dimensions

L	32mm +0.5/-0.7mm
H	33mm +0.2/-0.7mm
T	18mm +0.6/-0.7mm
S	27.5mm +/-0.4mm
LL	6mm +0/-2mm
F	0.8mm +/-0.05mm

Packaging Specifications

Packaging	Bulk, Box
Packaging Quantity	80

General Information

Series	C4AQ-M
Dielectric	Metallized Polypropylene
Style	Radial
RoHS	Yes
Lead	Wire Leads
Qualifications	AEC-Q200, IEC61071, EN61071, VDE0560
AEC-Q200	Yes
Component Weight	28.3 g
Miscellaneous	Rth = 27 C/W.

Specifications

Capacitance	8.5 uF
Capacitance Tolerance	5%
Voltage DC	800 VDC
Temperature Range	-55/+105°C
Rated Temperature	85°C
Insulation Resistance	3.5 GOhms
Max dV/dt	65 V/us
Resistance	7.1 mOhms (10kHz 70C)
Ripple Current	11.8 Amps Irms (10kHz 70C), 553 Amps Ipk
Inductance	27 nH

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)