

GR900 SMD Space, Ceramic, 1500 pF, 10%, 100 VDC, BX, N/A, 0805





Click	here	for	the	3D	model.

Dimensions	
Chip Size	0805
L	2.03mm +/-0.38mm (0.08 in +/-0.015 in)
W	1.27mm +/-0.38mm (0.05 in +/-0.015 in)
Т	1.4mm MAX (0.055 in MAX)
В	0.51mm +/-0.25mm (0.02 in +/-0.01 in)

Packaging Specifications	
Packaging	Bulk, Bag

General Information		
Series	GR900 SMD Space	
Style	SMD Chip	
RoHS	No	
Prop 65	▲ WARNING: Cancer and reproductive harm – http://www.p65warnings.ca.gov.	
SCIP Number	4848e250-8508-4d7b-8b2c-b2000a1148f1	
Termination	Lead (SnPb)	
Failure Rate	N/A	
Testing and Reliability	Mil-PRF-123 Group A	
Qualifications	MIL-PRF-123 Group A	
AEC-Q200	No	
Shelf Life	78 Weeks	
MSL	1	

Specifications	
Capacitance	1500 pF
Capacitance Tolerance	10%
Voltage DC	100 VDC
Temperature Range	-55/+125°C
Temperature Coefficient	BX

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

## 单击下面可查看定价,库存,交付和生命周期等信息

## >>KEMET(基美)