

T540D475K063CH6710

T540 HRA, Tantalum, Polymer Tantalum, HRA, 4.7 uF, 10%, 63 VDC, SMD, Polymer, Molded, High Reliability, C (0.01%/1000 Hrs), 120 mOhms, 7343, Height Max = 3.1mm


CATHODE (-) END VIEW




В




ANODE (+) END VIEW





т



Termination cutout at KEMET's option, either end

Click here for the 3D model.

| Dimensions | |
|------------|-----------------|
| Footprint | 7343 |
| L | 7.3mm +/-0.3mm |
| W | 4.3mm +/-0.3mm |
| Н | 2.8mm +/-0.3mm |
| т | 0.13mm REF |
| S | 1.3mm +/-0.3mm |
| F | 2.4mm +/-0.1mm |
| А | 3.8mm MIN |
| В | 0.5mm +/-0.15mm |
| E | 3.5mm REF |
| G | 3.5mm REF |
| Р | 0.9mm REF |
| R | 1mm REF |
| Х | 0.1mm +/-0.1mm |
| | |

| Packaging Specifications | |
|--------------------------|------------|
| Packaging | T&R, 178mm |
| Packaging Quantity | 500 |

| General Informatio | n |
|---------------------|-----------------------------------------------------------------------------|
| Series | T540 HRA |
| Dielectric | Polymer Tantalum |
| Style | SMD Chip |
| Description | SMD, Polymer, Molded, High Reliability |
| Features | Non-Combustible, Low ESR, High Reliability |
| RoHS | No |
| Prop 65 | A WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov. |
| SCIP Number | b064b03e-bd75-42af-b342-1fe94dec2340 |
| Termination | Solder Coated |
| AEC-Q200 | No |
| Component Weight | 352.36 mg |
| Shelf Life | 52 Weeks |
| MSL | 3 |

| Specifications | |
|----------------------------|----------------------------------------------------------------------------------------|
| Capacitance | 4.7 uF |
| Capacitance Tolerance | 10% |
| Voltage DC | 63 VDC (105C), 42.21 VDC (125C) |
| Temperature Range | -55/+125°C |
| Rated Temperature | 105°C |
| Humidity | 60C, 90% RH, 500 Hours, rated voltage |
| Dissipation Factor | 10% 120Hz 25C |
| Failure Rate | C (0.01%/1000 Hrs) |
| Resistance | 120 mOhms (100kHz 25C) |
| Ripple Current | 1369 mA (rms, 100kHz 45C) |
| Leakage Current | 30 uA (5min 25°C) |
| Testing and Reliability | 10 Cycles Surge Current Testing At -55C +0C/- 5C And +85C +/-5C After Voltage Aging |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)