

KEMET Part Number: R47I2470JE02M
(474I2470JE02M)

R47 X2 440 VAC, Film, Metallized Polypropylene, Automotive Safety, 0.047 uF, 20%, 440 VAC (X2), 1000 VDC, 110°C, Lead Spacing = 15mm



General Information

| | |
|------------------------|------------------------------|
| Series: | R47 X2 440 VAC |
| Dielectric: | Metallized Polypropylene |
| Style: | Radial |
| Features: | Automotive Grade, EMI Safety |
| RoHS: | Yes |
| Lead: | Cut |
| Safety Class: | X2 |
| Qualifications: | AEC-Q200, ENEC, UL, cUL |
| AEC-Q200: | Yes |

Dimensions

| | |
|-----------|--------------------|
| L | 18mm +0.3/-0.5mm |
| H | 17.5mm +0.1/-0.5mm |
| T | 6mm +0.2/-0.5mm |
| S | 15mm +/-0.4mm |
| LL | 4mm +0.5mm |
| F | 0.6mm +/-0.05mm |

Specifications

| | |
|-------------------------------|--------------|
| Capacitance: | 0.047 uF |
| Capacitance Tolerance: | 20% |
| Voltage AC: | 440 VAC (X2) |
| Voltage DC: | 1000 VDC |
| Temperature Range: | -40/+110°C |
| Rated Temperature: | 110°C |
| Dissipation Factor: | 0.1% 1kHz |
| Insulation Resistance: | 100 GOhms |
| Max dV/dt: | 600 V/us |

Packaging Specifications

| | |
|----------------------------|-----------|
| Packaging: | Bulk, Bag |
| Packaging Quantity: | 1000 |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)