
KEMET Part Number: 065MS26ACMK1STD

(A902GP065K260A)



MS/A902, Aluminum Electrolytic, 65 uF, 10%, 260 VAC, -20/+60°C



General Information		
Series:	MS/A902	
Dielectric:	Aluminum Electrolytic	
Description:	Motor Start Aluminum Electrolytic	
RoHS:	Yes	
Lead:	Quick Connect	
AEC-Q200:	No	
Halogen Free:	Yes	
Shelf Life:	156 Weeks	

Dimensions	
D	38mm +/-0.5mm
L	116mm MAX

Packaging Specifications	
Packaging:	Bulk, Bag

Specifications	
Capacitance:	65 uF
Capacitance Tolerance:	10%
Voltage AC:	260 VAC
Temperature Range:	-20/+60°C
Rated Temperature:	60°C
Life:	500 Hrs

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



ว5774

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)