



Click [here](#) for the 3D model.

Dimensions

D	3.51mm +/-0.25mm
L	9.91mm +/-0.38mm
LL	38.1mm +/-6.35mm
F	0.41mm +0.13/-0.03mm

Packaging Specifications

Packaging	Bulk, Box
Packaging Quantity	150

General Information

Series	T222 CSR09
Dielectric	MnO ₂ Tantalum
Style	Axial Hermetic
Description	Axial, Solid Tantalum, Hermetically Sealed, Military, Polar, Miniature, CSR09 Style
Features	Miniature, Polar
RoHS	No
Prop 65	⚠ WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov .
SCIP Number	bee1eed4-5fec-4214-9f43-620c5b22071f
Termination	Lead (SnPb)
Lead	Wire Leads
Qualifications	MIL-PRF-39003, CSR09
AEC-Q200	No
Construction	Hermetic
Notes	Dimensions Include Insulating Sleeve. Positive Lead: Alloy 52 (Solder Coated). Negative Lead: Solder Coated Nickel.

Specifications

Capacitance	15 uF
Capacitance Tolerance	10%
Voltage DC	10 VDC (85C), 9 VDC (125C Surge), 0.1 VDC (125C Reverse)
Temperature Range	-55/+125°C
Dissipation Factor	6%
Failure Rate	D (0.001%/1000 Hrs)
Resistance	3.7 Ohms (100kHz)
Ripple Current	156 mAmps (100kHz)
Leakage Current	2.5 uA
Testing and Reliability	Standard Testing To MIL-PRF-39003

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)