

KEMET Part Number: PHE840EF6820KF11R06L2
(F840FE824K300C)

PHE840E/F840, Film, Metallized Polypropylene, Safety, 0.82 uF, 10%, 300 VAC (X2), 760 VDC, 105°C, Lead Spacing = 27.5mm



Dimensions

| | |
|----|-----------------|
| L | 31.5mm MAX |
| H | 20.5mm MAX |
| T | 10.5mm MAX |
| S | 27.5mm +/-0.4mm |
| LL | 6mm NOM |
| F | 0.8mm NOM |

Packaging Specifications

| | |
|----------------------------|------|
| Packaging: | Tray |
| Packaging Quantity: | 216 |

General Information

| | |
|-------------------------|--|
| Series: | PHE840E/F840 |
| Dielectric: | Metallized Polypropylene |
| Style: | Radial |
| Features: | EMI Safety |
| RoHS: | Yes |
| Lead: | Wire Leads |
| Safety Class: | X2 |
| Qualifications: | ENEC, UL, cUL |
| AEC-Q200: | No |
| THB Performance: | No |
| Notes: | Not For New Design, Please Check Possible Alternative Parts (AltPart). |

Specifications

| | |
|-------------------------------|-----------------------|
| Capacitance: | 0.82 uF |
| Capacitance Tolerance: | 10% |
| Voltage AC: | 300 VAC (X2) |
| Voltage DC: | 760 VDC |
| Temperature Range: | -55/+105°C |
| Rated Temperature: | 105°C |
| Dissipation Factor: | 0.1% 1kHz, 0.4% 10kHz |
| Insulation Resistance: | 12.1951 GOhms |
| Max dV/dt: | 100 V/us |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)