


## VC1206K201R014

VC, Varistors, Low Voltage, 18 V, 14 VAC, 22 V, 38 V, 1 A, 200 A, 600 mJ, 8000 uW  $\,$ 



Click here for the 3D model.

Dimensions	
Chip Size	1206
L	3.2mm +/-0.3mm
W	1.6mm +/-0.2mm
Т	0.85mm MAX
В	0.5mm +/-0.25mm

Packaging Specifications	
Packaging	T&R
Packaging Quantity	4000

General Information	
Series	VC
Туре	Varistors
Style	SMD Chip
Description	Surface Mount Varistors
Features	Low Voltage
Termination	Nickel Tin
RoHS	Yes
Qualifications	IEC, UL, AEC-Q200
AEC-Q200	Yes

Specifications		
Specifications		
Voltage DC	18 VDC (25C)	
Voltage AC	14 VAC	
Temperature Range	-55/+125°C	
Storage Temperature Range	-55/+150°C	
Varistor Voltage	22 VDC at 1 mA	
Clamping Voltage	38 V	
Clamping Current	1 A (8/20 us MAX)	
Surge Current	200 A (8/20 us MAX)	
Energy	0.6 J (10/1000 us MAX)	
Capacitance	950 pF (1kHz)	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

## 单击下面可查看定价,库存,交付和生命周期等信息

## >>KEMET(基美)