


FLLE2100APVT6

KEMET, FLLE2-PV, EMI/RFI Filters, Noise Suppression, 1.2 kV, 100 A, 190x125x95mm



Click here for the 3D model.

Dimensions	
L	190mm NOM
W	125mm NOM
Н	95mm NOM
L1	220mm NOM
L2	203mm NOM
W1	90mm NOM
W2	100mm NOM
K	6.5mm NOM
M (Earth)	Threaded Studs M8

Packaging Specifications	
Packaging	Bulk
Packaging Quantity	1
Component Weight	2.5 kg

General Information	
Series	FLLE2-PV
Style	Chassis Mount
Description	EMI Filter, With Y Capacitor
Features	Single Phase, Photovoltaic Applications
Phase	Single-phase
RoHS	Yes
Qualifications	IEC/EN 60939, UL 1283
Terminal Type	Threaded Studs M8

Specifications	
Voltage DC	1200 VDC
Rated Current	100 A (50°C)
Rated Temperature	55°C
Temperature Range	-40/+100°C
Climate Category	40/100/21
Test Voltage DC (P to P)	1300 VDC
Test Voltage DC (P to E)	1300 VDC
Power Loss	15 W (25°C 50 Hz)

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)