




VRR Indust X7R HVHT200C, Ceramic, 1800 pF, 10%, 5000 VDC, X7R, Commercial, High Temperature, HighVoltage, Lead Spacing = 10.16mm



Click here for the 3D model.

Dimensions	
L	13.2mm MAX
W	12.7mm MAX
т	7.62mm MAX
S	10.16mm +/-0.051mm
LL	3.175mm MIN
F	0.635mm +/-0.051mm

Packaging Specifications			
Packaging	Bulk, Bag		
Packaging Quantity	1		

General Information	n
Series	VRR Indust X7R HVHT200C
Style	Radial
Description	Commercial, High Temperature, HighVoltage
Features	Commercial
RoHS	No
Prop 65	A WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov.
SCIP Number	8b930311-e6ed-4436-9857-2b5f449be092
Termination	Lead (SnPb)
Failure Rate	N/A
Testing and Reliability	Standard
AEC-Q200	No

Specifications			
Capacitance	1800 pF		
Capacitance Tolerance	10%		
Voltage DC	5000 VDC		
Dielectric Withstanding Voltage	7500 VDC		
Temperature Range	-55/+200°C		
Temperature Coefficient	X7R		
Dissipation Factor	2.5%1kHz1.0Vrms		
Insulation Resistance	100 GOhms		

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)