

## R60EI4470DQ30M

Aliases (60EI4470DQ30M)

R60, Film, Metallized Polyester, Automotive Grade, 4.7 uF, 20%, 100 VDC, 85°C, Lead Spacing = 15mm



| General Information |   |
|---------------------|---|
| Series              | R60   |
| Dielectric          | Metallized Polyester  |
| Style               | Radial  |
| Features            | Automotive Grade, DC Multipurpose Applications  |
| RoHS                | Yes   |
| Lead                | Wire Leads  |
| Qualifications      | AEC-Q200  |
| AEC-Q200            | Yes   |
| Component Weight    | 2.94 g  |
| Miscellaneous       | Upper Operating Temperature Of 125C Is Allowed For A Maximum Operating Time Of 1,000 Hours. Above 85C, DC And AC Voltage Derating Is 1.25%/C. |

Click [here](#) for the 3D model.

| Dimensions |                 |
|------------|-----------------|
| L          | 18mm +0.5mm     |
| H          | 19mm +0.1mm     |
| T          | 11mm +0.2mm     |
| S          | 15mm +/-0.4mm   |
| H0         | 18.5mm +/-0.5mm |
| F          | 0.8mm +/-0.05mm |

| Packaging Specifications |                         |
|--------------------------|-------------------------|
| Packaging                | Ammo, 360x340x59mm, Box |
| Packaging Quantity       | 340                     |

| Specifications        |            |
|-----------------------|------------|
| Capacitance           | 4.7 uF     |
| Capacitance Tolerance | 20%        |
| Voltage AC            | 63 VAC     |
| Voltage DC            | 100 VDC    |
| Temperature Range     | -55/+105°C |
| Rated Temperature     | 85°C       |
| Dissipation Factor    | 1% 1kHz    |
| Insulation Resistance | 266 MOhms  |
| Max dV/dt             | 3 V/us     |
| Inductance            | 10 nH      |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)