

**KEMET Part Number: PHE840MR7220JR05R06L2**  
(F840RF225J275C)

PHE840M/F840, Film, Metallized Polypropylene, Safety, 2.2 uF, 5%, 275 VAC (X2), 760 VDC, 105°C, Lead Spacing = 37.5mm



#### Dimensions

|    |                 |
|----|-----------------|
| L  | 41mm MAX        |
| H  | 24mm MAX        |
| T  | 13mm MAX        |
| S  | 37.5mm +/-0.5mm |
| LL | 6mm NOM         |
| F  | 1mm NOM         |

#### Packaging Specifications

|                     |      |
|---------------------|------|
| Packaging:          | Tray |
| Packaging Quantity: | 140  |

#### General Information

|                  |  |
|------------------|--|
| Series:          | PHE840M/F840   |
| Dielectric:      | Metallized Polypropylene   |
| Style:           | Radial   |
| Features:        | EMI Safety   |
| RoHS:            | Yes  |
| Lead:            | Wire Leads   |
| Safety Class:    | X2   |
| Qualifications:  | ENEC, UL, cUL  |
| AEC-Q200:        | No   |
| THB Performance: | No   |
| Notes:           | Not For New Design, Please Check Possible Alternative Parts (AltPart). |

#### Specifications

|                        |                       |
|------------------------|-----------------------|
| Capacitance:           | 2.2 uF                |
| Capacitance Tolerance: | 5%                    |
| Voltage AC:            | 275 VAC (X2)          |
| Voltage DC:            | 760 VDC               |
| Temperature Range:     | -55/+105°C            |
| Rated Temperature:     | 105°C                 |
| Dissipation Factor:    | 0.1% 1kHz, 0.8% 10kHz |
| Insulation Resistance: | 4.5454 GOhms          |
| Max dV/dt:             | 100 V/us              |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)