
KEMET Part Number: CAN18X393GAGACTU

(CAN18X393GAGAC7800)



CAN SMD Indust 250, Ceramic, 0.039 uF, 2%, C0G, SMD Chip, MLCC, AC Rated, 1812



	`B		RoHS:	Yes
			Termination:	Flexible Termination
			Marking:	No
			AEC-Q200:	No
			MSL:	1
Dimensions			Specifi	cations
Chin Sizo	1012		Capacitance:	0.039 uF

Dimensions			
Chip Size	1812		
L	4.5mm +/-0.4mm		
W	3.2mm +/-0.3mm		
Т	2.5mm +/-0.20mm		
В	0.7mm +/-0.35mm		

Packaging Specifications			
Packaging:	T&R, 180mm, Paper Tape		
Packaging Quantity:	500		

Specifications		
Capacitance:	0.039 uF	
Measurement Condition:	1 kHz 1.0Vrms	
Capacitance Tolerance:	2%	
Voltage AC:	250 VAC	
Dielectric Withstanding Voltage:	945 VDC	
Temperature Range:	-55/+125°C	
Temperature Coefficient:	COG	
Capacitance Change with Reference to +25°C and 0 VDC Applied (TCC):	15%, 1kHz 1.0Vrms	
Dissipation Factor:	0.1% 1 kHz 1.0Vrms	
Aging Rate:	0% Loss/Decade Hour	
Insulation Resistance:	10 GOhms	

General Information

CAN SMD Indust 250

SMD Chip, MLCC, AC Rated

Temperature Stable, Class I

SMD Chip

Series:

Style:

Description:

Features:

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



4687d

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)