


## MPCH1055L1R3

Aliases (UPIC1055L1R300)

KEMET, MPCH, Power, 1.3 uH, 20%, 1055(4639)



Click [here](#) for the 3D model.

### Dimensions

L	11.7mm MAX
W	10mm +/-0.3mm
T	5.5mm MAX
LL	2.1mm NOM
G	3mm +/-0.5mm

### Packaging Specifications

Packaging	T&R, 380mm
Packaging Quantity	500

### General Information

Series	MPCH
Style	SMD
Chip Size	1055(4639)
Description	Shielded, Surface Mount Inductor
Features	Large Current Inductors
RoHS	Yes
Core	Composite
Miscellaneous	40 (K) Temperature Rise Max.

### Specifications

Inductance	1.3 uH
Inductance Tolerance	20%
Temperature Range	-40/+125°C
Rated Temperature	120°C
Shielded	Yes
Current	17 A (Isat, 20% Drop In Inductance), 18.5 A (Irms, 40C Rise By Self Heating)
DC Resistance	2.3 mOhms

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)