
KEMET Part Number: R73RN2220SE00J

(73RN2220SE00J)



R73, Film, Film/Foil Polypropylene, Automotive Grade, 0.022 uF, 5%, 1250 VDC, 85°C, Lead Spacing = 22.5mm



R73
Film/Foil Polypropylene
Radial
Automotive Grade, Pulse
Yes
Cut
AEC-Q200
Yes
Above 85C DC And AC Voltage Derating Is 1.25%/C.

General Information

Dimensions		
L	26.5mm +0.3/-0.5mm	
Н	17mm +0.1/-0.5mm	
Т	8.5mm +0.2/-0.5mm	
S	22.5mm +/-0.4mm	
LL	4mm +2mm	
F	0.8mm +/-0.05mm	

Packaging Specifications		
Packaging:	Bulk, Bag	
Packaging Quantity:	468	

Specifications	
Capacitance:	0.022 uF
Capacitance Tolerance:	5%
Voltage AC:	450 VAC
Voltage DC:	1250 VDC
Temperature Range:	-55/+105°C
Rated Temperature:	85°C
Dissipation Factor:	0.03% 1kHz, 0.04% 10kHz, 0.1% 100kHz
Insulation Resistance:	100 GOhms
Max dV/dt:	11000 V/us
Inductance:	18 nH

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)