
## KEMET Part Number: PMR205AC7100M047R06

(P405CP105M125CH470)



PMR205/P405, Film, Metallized Paper, Resistor/Capacitor, 1 uF, 20%, 250 VDC, 85°C, Lead Spacing = 20.3mm



Dimensions		
L	24mm MAX	
Н	16.5mm MAX	
Т	11.3mm MAX	
S	20.3mm +/-0.4mm	
LL	6mm -1mm	
F	0.8mm +/-0.05mm	

Packaging Specifications	
Packaging:	Bulk, Bag
Packaging Quantity:	1080

General Information	
Series:	PMR205/P405
Dielectric:	Metallized Paper
Style:	Radial
Features:	RC Unit not approved
RoHS:	Yes
Lead:	Wire Leads
AEC-Q200:	No
Construction:	Molded
Miscellaneous:	Resistor Tolerance: +/-30%. Resistor= 47 Ohms.

Specifications		
Capacitance:	1 uF	
Capacitance Tolerance:	20%	
Voltage AC:	125 VAC	
Voltage DC:	250 VDC	
Temperature Range:	-40/+85°C	
Rated Temperature:	85°C	
Insulation Resistance:	1 GOhms	
Safety Class:	X2	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)