


VE1206K121R060

VE, Varistors, Low Voltage High Temperature, 85 V, 60 VAC, 100 V, 167 V, 1 A, 120 A, 900 mJ, 8000 uW



Click here for the 3D model.

Dimensions	
Chip Size	1206
L	3.2mm +/-0.3mm
W	1.6mm +/-0.2mm
Т	1.65mm MAX
В	0.5mm +/-0.25mm

Packaging Specifications		
Packaging	T&R	
Packaging Quantity	2000	

General Information		
Series	VE	
Туре	Varistors	
Style	SMD Chip	
Description	Surface Mount Varistors	
Features	Low Voltage High Temperature	
Termination	Nickel Tin	
RoHS	Yes	
Qualifications	IEC, UL, AEC-Q200	
AEC-Q200	Yes	

Specifications	
Voltage DC	85 VDC (25C)
Voltage AC	60 VAC
Temperature Range	-55/+150°C
Storage Temperature Range	-55/+150°C
Varistor Voltage	100 VDC at 1 mA
Clamping Voltage	167 V
Clamping Current	1 A (8/20 us MAX)
Surge Current	120 A (8/20 us MAX)
Energy	0.9 J (10/1000 us MAX)
Capacitance	330 pf (1kHz)

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)