
## KEMET Part Number: R73PR38204010K

(73PR38204010K)



R73, Film, Film/Foil Polypropylene, General Purpose, 0.82 uF, 10%, 630 VDC, 85°C, Lead Spacing = 27.5mm



General Information			
Series:	R73		
Dielectric:	Film/Foil Polypropylene		
Style:	Radial		
Features:	Pulse		
RoHS:	Yes		
Lead:	Wire Leads		
AEC-Q200:	No		
Miscellaneous:	Above 85C DC And AC Voltage Derating Is 1.25%/C.		

Dimensions				
L	32mm +0.3/-0.7mm			
Н	37mm +0.1/-0.7mm			
Т	22mm +0.2/-0.7mm			
S	27.5mm +/-0.4mm			
LL	30mm +5mm			
F	0.8mm +/-0.05mm			

Dimensions			
		Capacitance:	0.82 uF
L	32mm +0.3/-0.7mm	Capacitance Tolerance:	10%
Н	37mm +0.1/-0.7mm	•	-
T		Voltage AC:   300	
ı	22mm +0.2/-0.7mm	Voltage DC:	630 VD
S	27.5mm +/-0.4mm		-55/+10
LL	30mm +5mm	Temperature Range:	-55/+10
-		Rated Temperature:	85°C
F	0.8mm +/-0.05mm	Dissipation Factor:	0.03%
		•	
		Insulation Resistance:	36.585

Packaging Specifications		
Packaging:	Tray	
Packaging Quantity:	112	

AC DC L05°C 1kHz, 0.06% 10kHz 54 GOhms Max dV/dt: 11000 V/us Inductance: 18 nH

**Specifications** 

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



## 单击下面可查看定价,库存,交付和生命周期等信息

## >>KEMET(基美)