


LDD Comm COG, Ceramic, 0.015 uF, 5%, 50 VDC, COG







Click here for the 3D model.

Dimensions	
D	6.35mm +/-0.38mm
L	12.7mm +/-0.51mm
LL	38.1mm MIN
F	0.64mm +0.1/-0.025mm

Packaging Specifications			
Packaging	Bulk, Box		
Packaging Quantity	25		

General Information			
Series	LDD Comm COG		
Features	Commercial		
RoHS	No		
Prop 65	▲ WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov.		
SCIP Number	132e61c0-5a2b-4355-a818-8e6ea80949b5		
Termination	Lead (SnPb)		
Qualifications	EIA, UL		
AEC-Q200	No		

Specifications				
Capacitance	0.015 uF			
Capacitance Tolerance	5%			
Voltage DC	50 VDC			
Dielectric Withstanding Voltage	125 VDC			
Temperature Range	-55/+125°C			
Temperature Coefficient	COG			
Dissipation Factor	0.1% 1 kHz 25C			
Insulation Resistance	67 MOhms			

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

## 单击下面可查看定价,库存,交付和生命周期等信息

## >>KEMET(基美)