


C4BSMBX4220ZFLJ

C4BS, Film, Metallized Polypropylene, Power, 2.2 uF, 5%, 550 VAC, 850 VDC, 70°C, Lead Spacing = 22mm



	General Information	
	Series	C4BS
	Dielectric	Metallized Polypropylene
	Style	Radial
	Features	IGBT Circuit
	RoHS	Yes
	Lead	Flat Tabs
	AEC-Q200	No
	Component Weight	92 g
	Miscellaneous	KEMET Style F Tabs.

Specifications				
Capacitance	2.2 uF			
Capacitance Tolerance	5%			
Voltage AC	550 VAC			
Voltage DC	850 VDC			
Temperature Range	-40/+85°C			
Rated Temperature	70°C			
Max dV/dt	758 V/us			
Resistance	1.9 mOhms (100kHz)			
Ripple Current	37 Amps (100kHz 70C), 1668 Amps (Peak)			
Inductance	43 nH			

Click here for the 3D model.

Dimensions				
L	42mm +1.5/-0.7mm			
н	45mm +0.2/-0.7mm			
т	30mm +0.4/-0.7mm			
S	22mm +/-0.2mm			
S1	16mm +/-0.2mm			
S2	28mm +/-0.2mm			
Р	6mm NOM			

Packaging Specifications		
Packaging	Bulk, Bag	
Packaging Quantity	32	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)