

F43(X2), Film, Metallized Polypropylene, Resistor/Capacitor, 0.047 uF, 20%, 100°C, Lead Spacing = 15mm



Dimensions

L	18mm +/-0.5mm
H	14.5mm +/-0.1mm
T	7.5mm +/-0.2mm
S	15mm +/-0.4mm
LL	4mm +2/-0mm
F	0.6mm +/-0.05mm

Packaging Specifications

Packaging:	Bulk, Bag
Packaging Quantity:	1000

General Information

Series:	F43(X2)
Dielectric:	Metallized Polypropylene
Style:	Radial
RoHS:	Yes
Qualifications:	ENEC, UL
AEC-Q200:	No

Specifications

Capacitance:	0.047 uF
Capacitance Tolerance:	20%
Voltage AC:	275 VAC
Temperature Range:	-40/+100°C
Rated Temperature:	100°C
Dissipation Factor:	0.1% 1kHz (23C)
Insulation Resistance:	10 GOhms

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)