



### General Information

Series	SCR-XV
Style	Through-Hole
Features	High Impedance, High Rated Voltage
RoHS	Yes
Qualifications	AEC-Q200
Notes	Lead Spacing (S/S1) Are For Reference Only.
Miscellaneous	Temperature Rise Maximum: 55 K
Core	Mn-Zn Ferrite

### Specifications

Voltage AC	1000 VAC/VDC
Voltage DC	1000 VDC
Inductance	0.75 mH
Current	8 A
Temperature Range	-40/+120°C
DC Resistance	8.98 mOhms

### Dimensions

D	30mm MAX
T	27.5mm MAX
H	19.9mm MAX
LL	3.5mm +/-0.5mm
S	17mm NOM
S1	19mm NOM
Wire Size	1mm

### Packaging Specifications

Packaging	Tray
Packaging Quantity	150
Component Weight	16.4 g

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)