


## 05HV25N272KN

Aliases (05HV25N272K)

HV RAD-LDD Indust COG HV, Ceramic, 2700 pF, 10%, 500 VDC, COG, Commercial, High Voltage, Lead Spacing = 14.61mm



Click here for the 3D model.

Dimensions	
L	17.02mm MAX
Н	15.24mm MAX
Т	6.89mm MAX
S	14.61mm +/-0.762mm
LL	3.175mm MIN
F	0.635mm +0.102/-0.051mm

Packaging Specifications	
Packaging	Waffle
Packaging Quantity	20

General Information		
Series	HV RAD-LDD Indust COG HV	
Style	Radial	
Description	Commercial, High Voltage	
Features	Commercial	
RoHS	With Exemptions	
REACH	SVHC (Pb - CAS 7439-92-1)	
SCIP Number	ef26097b-3862-4ee0-b0ad-404a563ece0f	
Termination	Nickel	
Failure Rate	N/A	
AEC-Q200	No	

Specifications	
Capacitance	2700 pF
Capacitance Tolerance	10%
Voltage DC	500 VDC
Dielectric Withstanding Voltage	750 VDC
Temperature Range	-55/+125°C
Temperature Coefficient	COG
Dissipation Factor	0.15%
Aging Rate	0% Loss/Decade Hour
Insulation Resistance	100 GOhms

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

## 单击下面可查看定价,库存,交付和生命周期等信息

## >>KEMET(基美)