
KEMET Part Number: SM30B104K501B

(SM30B104K501)



KPS SM SMD Indust X7R HV, Ceramic, 0.1 uF, 10%, 500 VDC, X7R, SMD, Fixed, High Volt, Low ESR, Leaded, Industrial, SM30



Dimensions		
Chip Size	SM30	
L	7.62mm +/-0.762mm	
W	3.81mm +/-0.381mm	
Т	3.556mm MAX	
Α	2.54mm MAX	
В	2.54mm +/-0.508mm	

Packaging Specifications		
Packaging:	Tray	
Packaging Quantity:	50	

General Information		
Series:	KPS SM SMD Indust X7R HV	
Style:	SMD Chip	
Description:	SMD, Fixed, High Volt, Low ESR, Leaded, Industrial	
Features:	High Voltage, Low ESR, Industrial Grade	
RoHS:	With Exemptions	
REACH:	SVHC (Pb – CAS 7439-92-1)	
Termination:	Silver	
Marking:	No	
AEC-Q200:	No	
Shelf Life:	78 Weeks	
MSL:	1	

Specifications		
Capacitance:	0.1 uF	
Capacitance Tolerance:	10%	
Voltage DC:	500 VDC	
Dielectric Withstanding Voltage:	750 VDC	
Temperature Range:	-55/+125°C	
Temperature Coefficient:	X7R	
Dissipation Factor:	2.5%	
Insulation Resistance:	10 GOhms	
Quality Factor:	3	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



4e3dc

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)