

## T496C684K050AHE7K0


**General Information** 

T496, Tantalum, MnO2 Tantalum, Fused, .68 uF, 10%, 50 VDC, SMD, MnO2, Molded, Fused, N/A, 7 Ohms, 6032, Height Max = 2.8mm


CATHODE (-) END VIEW




ANODE (+) END VIEW



SIDE VIEW





Series	T496
Dielectric	MnO2 Tantalum
Style	SMD Chip
Description	SMD, MnO2, Molded, Fused
Features	Integral Fuse
RoHS	No
Prop 65	A WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov.
SCIP Number	1dd2e1b8-26dd-4d52-927c-6f9d519011aa
Termination	Solder Coated
AEC-Q200	No
Component Weight	224.48 mg
Shelf Life	156 Weeks
MSL	1

Click here for the 3D model.

Dimensions	
Footprint	6032
L	6mm +/-0.3mm
W	3.2mm +/-0.3mm
Н	2.5mm +/-0.3mm
Т	0.13mm REF
S	1.3mm +/-0.3mm
F	2.2mm +/-0.1mm
А	3.1mm MIN
В	0.5mm +/-0.15mm
E	2.4mm REF
G	2.8mm REF
Р	0.9mm REF
R	1mm REF
Х	0.1mm +/-0.1mm

Т

Specifications	,
Capacitance	.68 uF
Capacitance Tolerance	10%
Voltage DC	50 VDC (85C), 33.5 VDC (125C)
Temperature Range	-55/+125°C
Rated Temperature	85°C
<b>Dissipation Factor</b>	4% 120Hz 25C
Failure Rate	N/A
Resistance	7000 mOhms (100kHz 25C)
Ripple Current	125 mA (rms, 100kHz 25C), 112.5 mA (rms, 85C), 50 mA (rms, 125C)
Leakage Current	0.5 uA (5min 25°C)

Packaging Specifications		
Packaging	T&R, 178mm	
Packaging Quantity	500	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)