
KEMET Part Number: CWR11HC336JDC



(T492D336J015DC4252)

T492 CWR11, Tantalum, MnO2 Tantalum, Military/High Reliability, 33 uF, 5%, 15 VDC, SMD, MnO2, Molded, Military Equivalent, D (0.001%/1000 Hrs), 900 mOhms, 7343, Height Max = 3.1mm



Dimensions	
Footprint	7343
L	7.3mm +/-0.3mm
W	4.3mm +/-0.3mm
Н	2.8mm +/-0.3mm
Т	0.13mm REF
S	1.3mm +/-0.3mm
F	2.4mm +/-0.1mm
В	0.5mm +/-0.15mm
E	3.5mm REF
G	3.5mm REF
K	1mm MIN
Р	0.5mm MIN
R	1mm REF
Х	0.1mm +/-0.1mm

Packaging Specifications		
Packaging:	T&R, 178mm	
Packaging Quantity:	500	

AEC-Q200: No Component Weight: 412.33 mg		
Dielectric: MnO2 Tantalum Style: SMD Chip Description: SMD, MnO2, Molded, Military Equivalent RoHS: No Prop 65: Marce Cancer and reproductive harm - www.p65warnings.ca.gov. SCIP Number: 652b281f-d242-4453- bc44-0655d646cec3 Termination: Hot Solder Dipped Qualifications: MIL-PRF-55365/8, CWR11 Style AEC-Q200: No Note: When Option C Is Selected For Lead Material, Add An Additional 0.38mm To The Tolerances For "L", "W", "H", "K" ,"F" And "S".	General Information	
Style: SMD Chip Description: SMD, MnO2, Molded, Military Equivalent RoHS: No Prop 65: MARNING: Cancer and reproductive harm - www.p65warnings.ca.gov. SCIP Number: 652b281f-d242-4453- bc44-0655d646cec3 Termination: Hot Solder Dipped Qualifications: MIL-PRF-55365/8, CWR11 Style AEC-Q200: No Notes: Note: When Option C Is Selected For Lead Material, Add An Additional 0.38mm To The Tolerances For "L", "W", "H", "K" ,"F" And "S".	Series:	T492 CWR11
Description: SMD, MnO2, Molded, Military Equivalent RoHS: No Prop 65: WARNING: Cancer and reproductive harm - www.p65warnings.ca.gov. SCIP Number: 652b281f-d242-4453- bc44-0655d646cec3 Termination: Hot Solder Dipped Qualifications: MIL-PRF-55365/8, CWR11 Style AEC-Q200: No Note: Note: When Option C Is Selected For Lead Material, Add An Additional 0.38mm To The Tolerances For "L", "W", "H", "K" ,"F" And "S".	Dielectric:	MnO2 Tantalum
Description: Equivalent RoHS: No Prop 65: Marxing: Cancer and reproductive harm - www.p65warnings.ca.gov. SCIP Number: 652b281f-d242-4453- bc44-0655d646cec3 Termination: Hot Solder Dipped Qualifications: MIL-PRF-55365/8, CWR11 Style AEC-Q200: No Notes: Note: When Option C Is Selected For Lead Material, Add An Additional 0.38mm To The Tolerances For "L", "W", "H", "K" ,"F" And "S".	Style:	SMD Chip
Prop 65: A WARNING: Cancer and reproductive harm - www.p65warnings.ca.gov. SCIP Number: 652b281f-d242-4453- bc44-0655d646cec3 Termination: Hot Solder Dipped Qualifications: MIL-PRF-55365/8, CWR11 Style AEC-Q200: No Component Weight: 412.33 mg Notes: Note: When Option C Is Selected For Lead Material, Add An Additional 0.38mm To The Tolerances For "L", "W", "H", "K" ,"F" And "S".	Description:	-
Prop 65: and reproductive harm - and reproductive harm - www.p65warnings.ca.gov. SCIP Number: 652b281f-d242-4453- bc44-0655d646cec3 bc44-0655d646cec3 Termination: Hot Solder Dipped Qualifications: MIL-PRF-55365/8, CWR11 Style AEC-Q200: No Component Weight: 412.33 mg Notes: Note: When Option C Is Selected For Lead Material, Add An Additional 0.38mm To The Tolerances For "L", "W", "H", "K" ,"F" And "S".	RoHS:	No
SCIP Number: bc44-0655d646cec3 Termination: Hot Solder Dipped Qualifications: MIL-PRF-55365/8, CWR11 Style AEC-Q200: No Component Weight: 412.33 mg Notes: Note: When Option C Is Selected For Lead Material, Add An Additional 0.38mm To The Tolerances For "L", "W", "H", "K" ,"F" And "S".	Prop 65:	and reproductive harm -
Qualifications: MIL-PRF-55365/8, CWR11 Style AEC-Q200: No Component Weight: 412.33 mg Note: When Option C Is Selected For Lead Material, Add An Additional 0.38mm To The Tolerances For "L", "W", "H", "K" ,"F" And "S".	SCIP Number:	
AEC-Q200: No Component Weight: 412.33 mg Note: When Option C Is Selected For Lead Material, Add An Additional 0.38mm To The Tolerances For "L", "W", "H", "K" ,"F" And "S".	Termination:	Hot Solder Dipped
Component Weight: 412.33 mg Note: When Option C Is Selected For Lead Material, Add An Additional 0.38mm To The Tolerances For "L", "W", "H", "K" ,"F" And "S".	Qualifications:	MIL-PRF-55365/8, CWR11 Style
Note: When Option C Is Selected For Lead Material, Add An Additional 0.38mm To The Tolerances For "L", "W", "H", "K" ,"F" And "S".	AEC-Q200:	No
For Lead Material, Add AnNotes:Additional 0.38mm To TheTolerances For "L", "W", "H","K" ,"F" And "S".	Component Weight:	412.33 mg
MSL: 1	Notes:	Additional 0.38mm To The Tolerances For "L", "W", "H",
	MSL:	1

Specifications		
Capacitance:	33 uF	
Capacitance Tolerance:	5%	
Voltage DC:	15 VDC (85C), 10.05 VDC (125C)	
Temperature Range:	-55/+125°C	
Rated Temperature:	85°C	
Dissipation Factor:	6% 120Hz 25C	
Failure Rate:	D (0.001%/1000 Hrs)	
Resistance:	0.9 Ohms (100kHz 25C)	
Leakage Current:	5 uA (5min 25°C)	
Testing and Reliability:	Surge Testing At -55C And +85C Before Weibull	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)