


**A770KE396M1HLAS042** A770, Polymer Aluminum, 39 uF, 20%, 50 VDC, -55/+125°C



0.2 Maximum

General Information	
Series	A770
Dielectric	Polymer Aluminum
Style	SMD Can
Description	Surface Mount, Polymer Aluminum
RoHS	Yes
Lead	V-Chip
Qualifications	AEC-Q200
AEC-Q200	Yes
Halogen Free	Yes

Specifications		
Capacitance	39 uF	
Capacitance Tolerance	20%	
Voltage DC	50 VDC	
Temperature Range	-55/+125°C	
Rated Temperature	125°C	
Life	2000 Hrs	
Resistance	42 mOhms (100kHz 20C)	
Ripple Current	1300 mAmps (100kHz 125C)	
Leakage Current	58.5 uA (2min 20°C)	

Dimensions	
D	8mm +/-0.5mm
L	6.7mm +/-0.3mm
W	8.3mm +/-0.2mm
н	8.3mm +/-0.2mm
С	9mm +/-0.2mm
Р	3.1mm NOM
R	0.8 – 1.1mm

T&R, 380mm

1000

## Packaging Specifications Packaging

Packaging Quantity

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)