



Click [here](#) for the 3D model.

### Dimensions

|    |                      |
|----|----------------------|
| D  | 8.89mm +/-0.51mm     |
| L  | 17.53mm +/-0.51mm    |
| LL | 38.1mm MIN           |
| F  | 0.64mm +0.1/-0.025mm |

### Packaging Specifications

|                    |           |
|--------------------|-----------|
| Packaging          | Bulk, Bag |
| Packaging Quantity | 10        |

### General Information

|             |  |
|-------------|--|
| Series      | LDD Comm COG   |
| RoHS        | No   |
| Prop 65     | <b>⚠ WARNING:</b> Cancer and reproductive harm - <a href="http://www.p65warnings.ca.gov">http://www.p65warnings.ca.gov</a> . |
| SCIP Number | 132e61c0-5a2b-4355-a818-8e6ea80949b5   |
| Termination | Lead (SnPb)  |
| AEC-Q200    | No   |
| Notes       | Lead Length Shown Is For Parts Supplied In Bulk, See Packaging Specifications For Lead Lengths When Not Provided In Bulk.    |

### Specifications

|                                 |                |
|---------------------------------|----------------|
| Capacitance                     | 0.068 uF       |
| Capacitance Tolerance           | 1%             |
| Voltage DC                      | 100 VDC        |
| Dielectric Withstanding Voltage | 250 VDC        |
| Temperature Range               | -55/+125°C     |
| Temperature Coefficient         | COG            |
| Dissipation Factor              | 0.1% 1 kHz 25C |
| Insulation Resistance           | 15 MOhms       |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)