



Click [here](#) for the 3D model.

### General Information

Series	T369
Dielectric	MnO <sub>2</sub> Tantalum
Style	Radial
Description	Radial, Solid Tantalum, Dipped, Military, MIL-PRF-49137/2, CX12 Style
RoHS	No
Prop 65	<b>⚠ WARNING:</b> Cancer and reproductive harm - <a href="http://www.p65warnings.ca.gov">http://www.p65warnings.ca.gov</a> .
SCIP Number	0c1392c3-c7b9-4178-827c-fa26617a3178
Termination	Lead (SnPb)
Lead	Formed
Qualifications	MIL-PRF-49137/2, CX12
AEC-Q200	No

### Specifications

Capacitance	1.5 uF
Capacitance Tolerance	10%
Voltage DC	25 VDC (85C), 1.25 VDC (85C Reverse)
Temperature Range	-55/+85°C
Dissipation Factor	5%
Leakage Current	0.5 uA (25°C)

### Dimensions

D	4.45mm MAX
W	6.35mm +/-0.64mm
H	8.89mm MAX
S	3.18mm +/-0.38mm
LL	4.75mm +/-0.81mm
F	0.51mm +/-0.05mm

### Packaging Specifications

Packaging	Bulk, Bag
Packaging Quantity	1000

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)