

## C1805C183M5RACTU

Aliases (C1805C183M5RAC7800)

SMD Comm X7R, Ceramic, 0.018 uF, 20%, 50 VDC, X7R, SMD, MLCC, Temperature Stable, Class II, 1805



Click [here](#) for the 3D model.

| Dimensions |                  |
|------------|------------------|
| Chip Size  | 1805             |
| L          | 4.5mm +/-0.5mm   |
| W          | 1.27mm +/-0.38mm |
| T          | 0.9mm +/-0.10mm  |
| B          | 0.6mm +/-0.35mm  |

  

| Packaging Specifications |                          |
|--------------------------|--------------------------|
| Packaging                | T&R, 180mm, Plastic Tape |
| Packaging Quantity       | 4000                     |

| General Information |   |
|---------------------|---|
| Series              | SMD Comm X7R                            |
| Style               | SMD Chip                                |
| Description         | SMD, MLCC, Temperature Stable, Class II |
| Features            | Temperature Stable, Class II            |
| RoHS                | Yes                                     |
| Termination         | Tin                                     |
| Marking             | No                                      |
| AEC-Q200            | No                                      |
| Component Weight    | 41 mg                                   |
| Shelf Life          | 78 Weeks                                |
| MSL                 | 1                                       |

| Specifications   |   |
|--|---|
| Capacitance  | 0.018 uF  |
| Measurement Condition  | 1 kHz 1.0Vrms                                   |
| Capacitance Tolerance  | 20%   |
| Voltage DC   | 50 VDC  |
| Dielectric Withstanding Voltage                                    | 125 VDC   |
| Temperature Range  | -55/+125°C                                      |
| Temperature Coefficient  | X7R   |
| Capacitance Change with Reference to +25°C and 0 VDC Applied (TCC) | 15%, 1kHz 1.0Vrms                               |
| Dissipation Factor   | 2.5% 1kHz 1.0Vrms                               |
| Aging Rate   | 3% Loss/Decade Hour: Referee Time is 1000 Hours |
| Insulation Resistance  | 55.5556 GOhms                                   |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)