
KEMET Part Number: R73TI12204000K

(73TI12204000K)



R73, Film, Film/Foil Polypropylene, Automotive Grade, 2200 pF, 10%, 1600 VDC, 85°C, Lead Spacing = 15mm



General Information	
Series:	R73
Dielectric:	Film/Foil Polypropylene
Style:	Radial
Features:	Automotive Grade, Pulse
RoHS:	Yes
Lead:	Wire Leads
Qualifications:	AEC-Q200
AEC-Q200:	Yes
Miscellaneous:	Above 85C DC And AC Voltage Derating Is 1.25%/C.

Dimensions		
L	18mm +0.3/-0.5mm	
Н	12mm +0.1/-0.5mm	
Т	6mm +0.2/-0.5mm	
S	15mm +/-0.4mm	
LL	30mm +5mm	
F	0.8mm +/-0.05mm	

18mm +0.3/-0.5mm	
12mm +0.1/-0.5mm	
6mm +0.2/-0.5mm	
15mm +/-0.4mm	
30mm +5mm	
0.8mm +/-0.05mm	

Packaging Specifications	
Packaging:	Bulk, Bag
Packaging Quantity:	900

Specifications	
Capacitance:	2200 pF
Capacitance Tolerance:	10%
Voltage AC:	450 VAC
Voltage DC:	1600 VDC
Temperature Range:	-55/+105°C
Rated Temperature:	85°C
Dissipation Factor:	0.03% 1kHz, 0.04% 10kHz, 0.1% 100kHz
Insulation Resistance:	100 GOhms
Max dV/dt:	34000 V/us
Inductance:	10 nH

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



© 2006 - 2022 KEMET

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)