


ESD-R-38SR-P

Aliases (UECESDR38SRP00)

KEMET, ESD-R-SR, EMI Cores, Noise Suppression



Click	here	for	the	3D	model.

Dimensions		
D	39.5mm MAX	
D2	18mm MIN	
Т	14mm MAX	

Packaging Specifications	
Packaging	Tray, Box
Packaging Quantity	200
Component Weight	53.3 g

General Information			
Series	ESD-R-SR		
Style	Round - Toroidal		
Cable Type	Round Cable		
Description	EMI Core Solid, Large-Size Ring Type, For Round Cables, Coated Type		
Features	High Impedance, Effectively Suppresses Radiation at 150 kHz, Low Frequency Noise		
RoHS	Yes		
Qualifications	UL94 V-2		
Case Color	Gray		
Materials	Mn-Zn		

Specifications	
Temperature Range	-25/+85°C
Effective Frequency	10 MHz (AM Band Range)

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)