
KEMET Part Number: 100HV34N390KN

(100HV34N390K)



HV RAD-LDD Indust COG HV, Ceramic, 39 pF, 10%, 10000 VDC, COG, Commercial, High Voltage, Lead Spacing = 27.76mm



Dimensions		
L	26.67mm MAX	
Н	12.7mm MAX	
Т	6.89mm MAX	
S	27.76mm +/-0.76mm	
LL	3.175mm MIN	
F	0.635mm +0.102/-0.051mm	

Packaging Specifications		
Packaging:	Bulk, Bag	
Packaging Quantity:	1	

General Information	
Series:	HV RAD-LDD Indust C0G HV
Style:	Radial
Description:	Commercial, High Voltage
Features:	Commercial
RoHS:	No
Prop 65:	warning: Cancer and reproductive harm - www.p65warnings.ca.gov.
SCIP Number:	ef26097b-3862-4ee0- b0ad-404a563ece0f
Termination:	Nickel
Failure Rate:	N/A
AEC-Q200:	No

Specifications		
Capacitance:	39 pF	
Capacitance Tolerance:	10%	
Voltage DC:	10000 VDC	
Dielectric Withstanding Voltage:	15000 VDC	
Temperature Range:	-55/+125°C	
Temperature Coefficient:	COG	
Dissipation Factor:	0.15%	
Insulation Resistance:	100 GOhms	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)