



C/CT-0306

Aliases (USEX030600000)

 $\mbox{KEMET, C/CT-0306, Current, Round - Snap-on, AC, High Performance, Compact, Slim, Flame Retardant } \\$





Click here for the 3D model.

Dimensions		
D	6mm	
L	28.8mm	
Н	28.3mm	
T	19.4mm	
LL	140mm +/-10mm	

Packaging Specifications			
Packaging	Tray		
Packaging Quantity	144		
Component Weight	23.7 g		

General Information		
Series	C/CT-0306	
Type	Current	
Style	Round - Snap-on	
Description	High Alternating Current Sensor	
Features	High Performance, Compact, Slim, Flame Retardant	
Lead	Cable Connector	
RoHS	Yes	

Specifications	
Temperature Range	-10/+60°C
Voltage DC	100 mV (Output, +/- 8 mV), 7.5 V (Output Protection)
Insulation Resistance	100 MOhms (At 500 VDC, between core and terminal)
Current	30 Amps (50Hz/60Hz)
Miscellaneous	Current Transformation Ratio = 3,000. Insulation Resistance = 500 VDC To 100 MOhms. Storage Temperature = -20/+75C.

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)