

## PHE426KB6330JR06

Aliases (F426BQ334J400C, PHE426KB6330JB11R06)

PHE426/F426, Film, Metallized Polypropylene, General Purpose, 0.33 uF, 5%, 400 VDC, 85°C, Lead Spacing = 15mm



Click [here](#) for the 3D model.

### Dimensions

|    |               |
|----|---------------|
| L  | 18mm MAX      |
| H  | 16mm MAX      |
| T  | 8.5mm MAX     |
| S  | 15mm +/-0.4mm |
| LL | 6mm NOM       |
| F  | 0.8mm NOM     |

### Packaging Specifications

|                    |           |
|--------------------|-----------|
| Packaging          | Bulk, Bag |
| Packaging Quantity | 600       |

### General Information

|                  |  |
|------------------|--|
| Series           | PHE426/F426  |
| Dielectric       | Metallized Polypropylene   |
| Style            | Radial   |
| Features         | Pulse  |
| RoHS             | Yes  |
| Lead             | Wire Leads   |
| AEC-Q200         | No   |
| Component Weight | 3.034 g  |
| Notes            | Not For New Design, Please Check Possible Alternative Parts (AltPart). |

### Specifications

|                       |                         |
|-----------------------|-------------------------|
| Capacitance           | 0.33 uF                 |
| Capacitance Tolerance | 5%                      |
| Voltage AC            | 220 VAC                 |
| Voltage DC            | 400 VDC, 296 VDC (105C) |
| Temperature Range     | -55/+105°C              |
| Rated Temperature     | 85°C                    |
| Dissipation Factor    | 0.05% 1kHz, 0.1% 10kHz  |
| Insulation Resistance | 100 GOHms               |
| Max dV/dt             | 200 V/us                |
| Inductance            | 6 nH                    |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)