
KEMET Part Number: ALS80A242QC500

(A381UE242M500A)



ALS80, Aluminum Electrolytic, 2,400 uF, 20%, 500 VDC, -40/+105°C



Dimensions	
D	90mm +/-1mm
L	67mm +/-2mm
Т	5.5mm +/-0.5mm
S	31.8mm +/-0.5mm
DT	13mm +/-0.5mm
LT	71.5mm +/-1mm
TD	10mm MIN
V	25mm NOM
Z	10mm NOM

Packaging Specifications		
Sleeving:	Yes	
Packaging:	Tray	

General Information		
Series:	ALS80	
Dielectric:	Aluminum Electrolytic	
Description:	Screw Terminal, Aluminum Electrolytic	
RoHS:	Yes	
AEC-Q200:	No	
Halogen Free:	Yes	
Component Weight:	615 g	
Notes:	Dimensions D And L Include Sleeving. MS (MxH) = M12x16. Mounting Clamp (Sold Separately): V90N	
Shelf Life:	156 Weeks	

Specifications		
Capacitance:	2,400 uF	
Capacitance Tolerance:	20%	
Voltage DC:	500 VDC, 550 VDC (Surge)	
Temperature Range:	-40/+105°C	
Rated Temperature:	105°C	
Life:	9000 Hrs (Rated Voltage And Ripple Current At 105C), 15000 Hrs (Rated Voltage At 105C)	
Resistance:	98 mOhms (100Hz 20C), 74 mOhms (10kHz 20C)	
Ripple Current:	9.4 Amps (100Hz 105C), 14.9 Amps (10 kHz 105C)	
Leakage Current:	3600 uA	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



© 2006 - 2022 KEMET

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)