
## **KEMET Part Number: R73PW4100SE00J**

(73PW4100SE00J)



R73, Film, Film/Foil Polypropylene, General Purpose, 1 uF, 5%, 630 VDC, 85°C, Lead Spacing = 37.5mm



General Information		
Series:	R73	
Dielectric:	Film/Foil Polypropylene	
Style:	Radial	
Features:	Pulse	
RoHS:	Yes	
Lead:	Cut	
AEC-Q200:	No	
Miscellaneous:	Above 85C DC And AC Voltage Derating Is 1.25%/C.	

**Specifications** 

Inductance:

20 nH

Dimensions		
L	41.5mm +0.3/-0.7mm	
Н	40mm +0.1/-0.7mm	
Т	20mm +0.3/-0.7mm	
S	37.5mm +/-0.4mm	
LL	4mm +2mm	
F	1mm +/-0.05mm	

ensions	• promounono	
	Capacitance:	1 uF
41.5mm +0.3/-0.7mm	Capacitance Tolerance:	5%
40mm +0.1/-0.7mm	Voltage AC:	300 VAC
20mm +0.3/-0.7mm	Voltage DC:	630 VDC
37.5mm +/-0.4mm	Temperature Range:	-55/+105°C
4mm +2mm	Rated Temperature:	85°C
1mm +/-0.05mm	Dissipation Factor:	0.03% 1kHz, 0.06% 10kHz
	Insulation Resistance:	30 GOhms
	Max dV/dt:	3000 V/us

Packaging Specifications		
Packaging:	Tray	
Packaging Quantity:	126	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



## 单击下面可查看定价,库存,交付和生命周期等信息

## >>KEMET(基美)