



Click [here](#) for the 3D model.

Dimensions

D	4.45mm +/-0.13mm
L	11.13mm +/-0.79mm
L2	15.49mm MAX
LL	38.1mm +/-6.35mm
F	0.51mm +/-0.05mm

Packaging Specifications

Packaging	Tray
Packaging Quantity	30

General Information

Series	T256 CSS33
Dielectric	MnO2 Tantalum
Style	Axial Hermetic
Description	Axial, Solid Tantalum, Hermetically Sealed, Military, CSS33 Style
Features	Extended Capacitance, Low Leakage, Low ESR, Low DF
RoHS	No
Prop 65	⚠ WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov
SCIP Number	bee1eed4-5fec-4214-9f43-620c5b22071f
Termination	Lead (SnPb)
Lead	Wire Leads
Qualifications	CSS33
AEC-Q200	No
Construction	Hermetic
Notes	Uninsulated. Caution: Black Band Indicates Negative End Of Case.

Specifications

Capacitance	33 uF
Capacitance Tolerance	10%
Voltage DC	15 VDC (85C), 12 VDC (125C Surge), 0.15 VDC (125C Reverse)
Temperature Range	-55/+125°C
Dissipation Factor	6%
Failure Rate	C (0.01%/1000 Hrs)
Resistance	0.24 Ohms (100kHz)
Ripple Current	645 mAmps (100kHz)
Leakage Current	1 uA

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)