
KEMET Part Number: ALS71A472NF500

(A490TM472M500A)



ALS71, Aluminum Electrolytic, 4,700 uF, 20%, 500 VDC, -40/+85°C



Dimensions	
D	77mm +/-1mm
L	105mm +/-2mm
Т	5.5mm +/-0.5mm
S	31.8mm +/-0.5mm
DT	13mm +/-0.5mm
LT	110.5mm +/-1mm
TD	10mm MIN
V	19mm NOM
Z	10mm NOM

Packaging Specifications		
Sleeving:	Yes	
Packaging:	Tray	

General Information		
Series:	ALS71	
Dielectric:	Aluminum Electrolytic	
Description:	Screw Terminal, Aluminum Electrolytic	
RoHS:	Yes	
Mounting:	Stud	
AEC-Q200:	No	
Halogen Free:	Yes	
Component Weight:	690 g	
Notes:	Dimensions D And L Include Sleeving. MS (MxH) = M12x16. Mounting Clamp (Sold Separately): V11	
Shelf Life:	156 Weeks	

Specifications	
Capacitance:	4,700 uF
Capacitance Tolerance:	20%
Voltage DC:	500 VDC, 550 VDC (Surge)
Temperature Range:	-40/+85°C
Rated Temperature:	85°C
Life:	20000 Hrs (Rated Voltage And Ripple Current At 85C), 40000 Hrs (Rated Voltage At 85C)
Resistance:	59 mOhms (100Hz 20C), 45 mOhms (10kHz 20C)
Ripple Current:	14.5 Amps (100Hz 85C), 21.1 Amps (10kHz 85C)
Leakage Current:	6000 uA

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)